



TefTEC™ Series Filter Cartridges

Absolute Rated PTFE Membrane Filter Cartridges

TefTEC cartridge filters are constructed with naturally hydrophobic PTFE membrane and polypropylene support layers and components. The HIMA retentive PTFE membrane offers superior hydrophobicity and water intrusion resistance compared to PVDF and polypropylene membranes, and the cartridge construction offers a cost-effective alternative to all-fluorocarbon filters. TefTEC filters are ideal for gas/vent applications and the filtration of aggressive chemicals and solvents.

FEATURES & BENEFITS

- High surface area, single-layer construction provides superior flow rates and minimizes filtration system size
- 100% Flushed with 18 MΩ-cm DI water and integrity tested
- Filters are manufactured, flushed, tested and packaged in an ISO Class 7 Cleanroom Environment
- Each filter element stamped with pore size, lot and serial number for identification and traceability
- Complete qualification guide available
- Available prewet for use with aqueous based chemicals

CERTIFICATIONS

- USP Class VI: Meets USP Class VI Biological Test for Plastics
- FDA Listed Materials: All materials comply with FDA Title 21 of the Code of Federal Regulations Sections 174.5, 177.1520, and 177.1550 as applicable for food and beverage contact.

TYPICAL APPLICATIONS

- Aggressive chemicals
- Tank Vents
- Hot DI water
- Strong acids/bases
- Compressed gases
- Pharmaceutical Intermediates
- Solvents
- Photoresists
- Fermentation air

PERFORMANCE SPECIFICATIONS

- Steam/Autoclave: Cartridges will withstand at least 100 steam/autoclave thirty-minute cycles @ 275°F (135°C)

Product Specifications

Media: Expanded PTFE Membrane

Inner core, end caps, cage: Polypropylene

Support layers: Polypropylene

Gaskets/O-Rings:

Buna-N, EPDM, Silicone, Teflon (gasket only),
Teflon Encapsulated Viton (O-Rings only), Viton

Micron ratings: 0.05, 0.1, 0.2, 0.45, 1.0 µm

Dimensions

Nominal lengths:

5" 9.75" 10" 20" 30" 40"
12.7 24.8 25.4 50.8 76.2 101.6 cm

Outside diameter: 2.7" (6.9 cm)

Inside diameter: 1.0" (2.54 cm)

Surface area: 8.5 ft² (0.79 m²) per 10" element

Operating Parameters

Maximum operating temperature:

203°F (95°C)

Maximum differential pressure:

80 psid @ 70°F (4.14 bar @ 21°C)


40 psid @ 160°F (2.8 bar @ 71°C)

Maximum reverse differential pressure:

40 psid @ 70°F (2.8 bar @ 21°C)

Recommended change-out pressure:

35 psid (2.4 bar)




TEFTEC NOMENCLATURE INFORMATION

Filter Type	Retention Rating (microns)		Nominal Length (inches)		End Configuration		Gasket or O-Ring	Options
TefTEC Series	0.05	0.45	-5	-20	P	Double Open End	B Buna-N	-W Pre-Wet
	0.1	1	-9.75*	-30	P2	226/Flat Single Open End	E EPDM	
	0.2		-10	-40	P3	222/Flat Single Open End	S Silicone	
					P7	226/Fin Single Open End	T Teflon	
					P8	222/Fin Single Open End	encap. Viton (O-Rings only)	
				AM	Single Open End, Internal O-Ring	V Viton		
				NPC	Double Open End, Internal O-Ring	S		
Example: TefTEC 0.1-20P2S-W								
TefTEC	0.1		-20		P2			-W

*Available only for DOE (P) configuration

TEFTEC FLOW RATE

Typical Flow Rate Clean Water at Ambient Temperature (per 10" cartridge)



For liquids other than water, multiply pressure drop by the fluid viscosity in centipoise


INTEGRITY TEST SPECIFICATIONS

Air Diffusion per 10-inch cartridge wet with 60/40 IPA/water. Contact Graver Technologies for specific method.

Pore Size	Specification
0.05 µm	≤ 50 cc/min @ 22 psig (1.5 bar)
0.1 µm	≤ 50 cc/min @ 18 psig (1.2 bar)
0.2 µm	≤ 20 cc/min @ 12 psig (0.8 bar)
0.45 µm	≤ 15 cc/min @ 5 psig (0.34 bar)
1.0 µm	≤ 15 cc/min @ 3 psig (0.2 bar)

TEFTEC AIR FLOW RATE


Air Flow Rate (per 10" cartridge)



Test conditions: System pressure at <10 psig (vent), 65°F (18°C), outlet open to atmosphere

TEFTEC AIR FLOW RATE

Air Flow Rate (per 10" cartridge)



Test conditions: System pressure at 30 psig, 65°F (18°C)

FOR MORE INFORMATION

Customer Service/ Technical Support: 1-888-353-0303

Europe (UK): +44-1424-777791 | China: +86-21-5238-6576 | Asia: +65-9635-7690

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believe to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. TefTEC is a trademark of Graver Technologies, LLC.

GTX-297 10-16

DISTRIBUTED BY



Graver Technologies | 302-731-1700 | 800-249-1990
info@gravertech.com | www.gravertech.com

A member of The Marmon Group—A Berkshire Hathaway Company