





Bag filter housing

STAINLESS STEEL AISI 316 BAG FILTER HOUSINGS

FILTRO FBA-4RS



FEATURES

Model	FILTRO FBA-4RS
Material	AISI 316
In/Out	DN 150 FLANGE ANSI

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	12 bar

Max working temperature	80°C
Life test	100.000 cycles from 0 to 8 bar

BAGS

(175/180 mm)
\ -1 /
n)
66 mm





RING TYPE

Internal ring	175/180 mm
Welded ring	175/180 mm

APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	In/Out	Bag's end cap	Quantity box	-
FBA4RS316070432M	FILTRO FBA-4RS 4x32"	Micropallinatura ceramica	DN 150 FLANGE ANSI	07	1	







Bag filter housing

STAINLESS STEEL AISI 316 BAG FILTER HOUSINGS

FILTRO FBA-4RS

HOUSINGS CODE LIST Model Material Ring diameter N° bags Bags height Specs and finishing 32" (810 mm) AISI 316 316 07 Diam. 7" 04 32 Ceramic blasted FBA4RS 07 (175/180 mm)



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

<u>Link to product's details pictures, installation pictures</u>

http://www.everblue.it/OtherInstallPics/INS FILTROFBA-01-4RS.PDF



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: ASME VIII