

## Bag filter housing

# STAINLESS STEEL AISI 316 BAG FILTER HOUSINGS

## FILTRO FBE

[Link to PDF Drawing](#)

 [//www.everblue.it/CadDrawings/F20170711122750496FBE31607MERGED.pdf](http://www.everblue.it/CadDrawings/F20170711122750496FBE31607MERGED.pdf)

### FEATURES

Model	FILTRO FBE
Material	AISI 316
In/Out	17" DN80 FLANGE EN1092 - 32" DN80 FLANGE EN1092

### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	12 bar
Max working temperature	80°C
Life test	100.000 cycles from 0 to 8 bar

### BAGS

N° bags	1
Ring diameter	07 Diam. 7" (175/180 mm)
Height	17" (430 mm) - 32" (810 mm)
Diametro interno minimo/massimo	161 mm / 166 mm
Outer diameter	180 mm



SI



SW

### RING TYPE

SI7 Internal ring	175/180 mm
SW7 Welded ring	175/180 mm

### APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	In/Out	Bag's end cap	Quantity box	-
FBE316070117M	FILTRO FBE 1x17"	Micropallinatura ceramica	17" DN80 FLANGE EN1092	07	1	
FBE316070132M	FILTRO FBE 1x32"	Micropallinatura ceramica	32" DN80 FLANGE EN1092	07	1	

## Bag filter housing

# STAINLESS STEEL AISI 316 BAG FILTER HOUSINGS

## FILTRO FBE

### HOUSINGS CODE LIST

Model	Material	Ring diameter	N° bags	Bags height	Specs and finishing
FBE	AISI 316 316	Ø7 Diam. 7" (175/180 mm) Ø7	1 Ø1	17" (430 mm) 32" (810 mm) 17 32	Ceramic blasted M



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*

[Link to product's details pictures, installation pictures](#)

[http://www.everblue.it/OtherInstallPics/INS\\_FILTROFBE-01.PDF](http://www.everblue.it/OtherInstallPics/INS_FILTROFBE-01.PDF)



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014.

These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

**Design code:** ASME VIII