

Housings for filter cartridges STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-01

[Link to PDF product's drawing](#)

 www.everblue.it/CadDrawings/F20170314151907817FBKE316BL0120M

FEATURES



Model	FILTRO FILTERBLACK FBKE-BL-01
Material	AISI 316 L
In/Out	DN 80 FLANGE EN1092

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	1
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FBKE316LBL0120M	FILTRO FILTERBLACK FBKE-BL-01 1x20"	Ceramic blasted	20"	DN 80 FLANGE EN1092	1000	BL	1	

Housings for filter cartridges STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-01

HOUSINGS CODE LIST

Model		Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FBKE		AISI 316 L 316L		BL BL		1 01		20" 20		Ceramic blasted M	



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: ASME VIII