

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMR-60


[Link to PDF product's drawing](http://www.everblue.it/CadDrawings/FMR316LST6040_I.pdf)
 (http://www.everblue.it/CadDrawings/FMR316LST6040_I.pdf)

FEATURES

Model	FILTRO FMR-60
Material	AISI 316 L
In/Out	DN 200 FLANGE L

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 6 bar

CARTRIDGES

N° cartridges	60
Type end caps	DOE (Standard)
Inner diameter min/max	26 mm / 30 mm
Outer diameter	68 mm
Cartridges height	40"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FMR316LST6040DP	FILTRO FMR-60 60x40"	Pickled, Passivated	40"	DN 200 FLANGE L	5000	ST	1	

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMR-60

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMR	AISI 316 L 316L	ST ST	60 60	40" 40	Pickled, Passivated DP



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

[Link to product's details pictures, installation pictures](#)

http://www.everblue.it/OtherInstallPics/INS_FILTEROFMR-60.PDF



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4