


Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMR-90


[Link to PDF product's drawing](http://www.everblue.it/CadDrawings/FMR316LST9040_I.pdf)
 (http://www.everblue.it/CadDrawings/FMR316LST9040_I.pdf)

FEATURES

Model	FILTRO FMR-90
Material	AISI 316 L
In/Out	DN 200 FLANGE L

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 6 bar

CARTRIDGES

N° cartridges	90
Type end caps	DOE (Standard)
Inner diameter min/max	26 mm / 30 mm
Outer diameter	68 mm
Cartridges height	40"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FMR316LST9040DP	FILTRO FMR-90 90x40"	Pickled, Passivated	40"	DN 200 FLANGE L	7500	ST	1	

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMR-90

HOUSINGS CODE LIST

Model		Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FMR		AISI 316 L	316L	ST	ST	90	90	40"	40	Pickled, Passivated	DP



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014 of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4