

## Housings for filter cartridges

# STAINLESS STEEL AISI 316 L HOUSINGS

# FILTRO FM0-BHF

[Link to PDF product's drawing](#)

 [www.everblue.it/CadDrawings/F20170203154221135FM0316LBHF0120\\_ME](http://www.everblue.it/CadDrawings/F20170203154221135FM0316LBHF0120_ME)

### FEATURES



Model	FILTRO FM0-BHF
Material	AISI 316 L
In/Out	1" ½ BSP F

### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	200.000 cycles from 0 to 10 bar

### CARTRIDGES

N° cartridges	1
Type end caps	BIG BHF
Inner diameter min/max	36 mm / 36 mm
Outer diameter	115 mm
Cartridges height	9" ¾ - 20"



### APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FM0316LBHF0109M	FILTRO FM0-BHF 1x9" ¾	Ceramic blasted	9" ¾	1" ½ BSP F	106	BHF	1	
FM0316LBHF0120M	FILTRO FM0-BHF 1x20"	Ceramic blasted	20"	1" ½ BSP F	106	BHF	1	

## Housings for filter cartridges

# STAINLESS STEEL AISI 316 L HOUSINGS

# FILTRO FM0-BHF

### HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FM0	AISI 316 L 316L	BHF BHF	1 01	9" ¾ 20"	Ceramic blasted M



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4