

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTRO FIB-68

FEATURES

Model	FILTRO FIB-68
Material	FRP
In/Out	DN 300 FLANGE DN8063PN16

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	50°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	68
Type end caps	DOE (Standard)
Inner diameter min/max	26 mm / 30 mm
Outer diameter	70 mm
Cartridges height	40"



APPLICATIONS

Water
Sea water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FIBFRPST6840WH	FILTRO FIB-68 68x40"	White	40"	DN 300 FLANGE DN8063PN16	5666	ST	1	

Housings for filter cartridges FIBERGLASS HOUSINGS FILTRO FIB-68

HOUSINGS CODE LIST

Model		Material	Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FIB		FRP (Fiberglass)	ST	ST	68	68	40"	40	White	WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: EN 13121-3