

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FIB-FON-09

[Link to PDF product's drawing](http://www.everblue.it/CadDrawings/CAD_FILTROFIB-FON-09.PDF)

 http://www.everblue.it/CadDrawings/CAD_FILTROFIB-FON-09.PDF

FEATURES

Model	FILTRO FIB-FON-09
Material	FRP
In/Out	DN 200 FLANGE L

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	50°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	9
Type end caps	FON
Inner diameter min	76 mm
Outer diameter	147,5 mm
Cartridges height	40"



APPLICATIONS

Water
Sea water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FIBFRPFON0940WH	FILTRO FIB-FON-09 9x40"	White	40"	DN 200 FLANGE L	5000	FON	1	

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FIB-FON-09

HOUSINGS CODE LIST

Model		Material	Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FIB		FRP (Fiberglass)	FON	FON	9	09	40"	40	White	WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

[Link to product's details pictures, installation pictures](#)

http://www.everblue.it/OtherInstallPics/INS_FILTROFIB-FON-09.PDF



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: EN 13121-3