

## Housings for filter cartridges

# STAINLESS STEEL AISI 316 L HOUSINGS

# FILTRO FM0-C7

[Link to PDF product's drawing](http://www.everblue.it/CadDrawings/FM0316LC70109_I_merged.pdf)

 [://www.everblue.it/CadDrawings/FM0316LC70109\\_I\\_merged.pdf](http://www.everblue.it/CadDrawings/FM0316LC70109_I_merged.pdf)

### FEATURES

Model	FILTRO FM0-C7
Material	AISI 316 L
In/Out	3/4" BSP F

### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	200.000 cycles from 0 to 10 bar

### CARTRIDGES

N° cartridges	1
Type end caps	Code 7 226 O-ring/spear
Inner diameter min	Not necessary
Outer diameter	70 mm
Cartridges height	9" 3/4 - 10" - 20" - 30" - 40"



### APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FM0316LC70109M	FILTRO FM0-C7 1x9" 3/4	Ceramic blasted	9" 3/4	3/4" BSP F	66	C7	1	
FM0316LC70110M	FILTRO FM0-C7 1x10"	Ceramic blasted	10"	3/4" BSP F	66	C7	1	
FM0316LC70120M	FILTRO FM0-C7 1x20"	Ceramic blasted	20"	3/4" BSP F	66	C7	1	
FM0316LC70130M	FILTRO FM0-C7 1x30"	Ceramic blasted	30"	3/4" BSP F	66	C7	1	
FM0316LC70140M	FILTRO FM0-C7 1x40"	Ceramic blasted	40"	3/4" BSP F	66	C7	1	

## Housings for filter cartridges

# STAINLESS STEEL AISI 316 L HOUSINGS

# FILTRO FM0-C7

### HOUSINGS CODE LIST

Model		Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FM0	AISI 316 L	316L	C7	C7	1	01	9" ¼ 10" 20" 30" 40"	09 10 20 30 40	Ceramic blasted	M	



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*

[Link to product's details pictures, installation pictures](#)

[http://www.everblue.it/OtherInstallPics/INS\\_FILTERFM0-C7-01.PDF](http://www.everblue.it/OtherInstallPics/INS_FILTERFM0-C7-01.PDF)



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4