


Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMC-03

[Link to PDF product's drawing](#)

 www.everblue.it/CadDrawings/F20150619120021308FMC316LST03_..._I_m

FEATURES

Model	FILTRO FMC-03
Material	AISI 316 L
In/Out	2" BSP M

DESIGN DATA

Max working pressure	8 bar
Hydraulic test pressure	12 bar
Max working temperature	80°C
Life test	100.000 cycles from 0 to 8 bar

CARTRIDGES

N° cartridges	3
Type end caps	DOE (Standard)
Inner diameter min/max	26 mm / 30 mm
Outer diameter	68 mm
Cartridges height	20" - 30" - 40"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FMC316LST0320M	FILTRO FMC-03 3x20"	Ceramic blasted	20"	2" BSP M	250	ST	1	
FMC316LST0330M	FILTRO FMC-03 3x30"	Ceramic blasted	30"	2" BSP M	250	ST	1	
FMC316LST0340M	FILTRO FMC-03 3x40"	Ceramic blasted	40"	2" BSP M	250	ST	1	

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMC-03

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMC	AISI 316 L 316L	ST ST	3 03	20" 30" 40"	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4