

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMG-15

 [Link to PDF product's drawing](http://www.everblue.it/CadDrawings/FMG316LST1540I.PDF)
 (http://www.everblue.it/CadDrawings/FMG316LST1540I.PDF)

FEATURES

Model	FILTRO FMG-15
Material	AISI 316 L
In/Out	DN 100 FLANGE L

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	15
Type end caps	DOE (Standard)
Inner diameter min/max	26 mm / 30 mm
Outer diameter	68 mm
Cartridges height	40"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FMG316LST1540DP	FILTRO FMG-15 15x40"	Pickled, Passivated	40"	DN 100 FLANGE L	1250	ST	1	

Housings for filter cartridges

STAINLESS STEEL AISI 316 L HOUSINGS

FILTRO FMG-15

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMG	AISI 316 L 316L	ST ST	15 15	40" 40	Pickled, Passivated DP



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

European Community members only.



These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4