

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FIB-FON-23

FEATURES

Model	FILTRO FIB-FON-23
Material	FRP
In/Out	DN 350 FLANGE DN8063PN16

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	50°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	23
Type end caps	FON
Inner diameter min	76 mm
Outer diameter	147,5 mm
Cartridges height	40"



APPLICATIONS

Water
Sea water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FIBFRPFON2340WH	FILTRO FIB-FON-23 23x40"	White	40"	DN 350 FLANGE DN8063PN16	15863	FON	1	

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FIB-FON-23

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FIB	FRP (Fiberglass)	FON FON	23 23	40"	40 White WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: EN 13121-3