

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FILTERBLUE-BL-02-2RS

[Link to PDF product's drawing](#)

www.everblue.it/CadDrawings/F20160728095018084FBL2RSFRPBL0420W

FEATURES



Model	FILTRO FILTERBLUE-BL-02-2RS
Material	FRP
In/Out	DN 125 FLANGE DN8063 PN16

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	4
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



APPLICATIONS

Water
Sea water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FBL2RSFRPBL0420WH	FILTRO FILTERBLUE-BL-02-2RS 4x20"	White	20"	DN 125 FLANGE DN8063 PN16	2333	BL	1	

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTRO FILTERBLUE-BL-02-2RS

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBL2RS	FRP (Fiberglass)	BL BL	4 04	20" 20	White WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

[Link to product's details pictures, installation pictures](#)

http://www.everblue.it/OtherInstallPics/INS_FILTERBLUE-BL-2-2RS.PDF



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014.

These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13

Design code: EN 13121-3 - ASME X (for body)