

Cyclon filters

CYCLON PVC FILTERS

SPEEDBLUE SPO

[Link to product's PDF drawing](http://www.everblue.it/CadDrawings/SPOPVC100MTWH_I_merged.pdf)

 http://www.everblue.it/CadDrawings/SPOPVC100MTWH_I_merged.pdf

FEATURES

Model	SPO
Material	PVC
Connections IN/OUT	1" BSP M, 1" ½ BSP M, 2" BSP M

DESIGN DATA

Min working pressure	1 bar
Max working pressure	6 bar
Pressure test	9 bar
Max working temperature	40°C
Max diameter inlet particles	5 mm

APPLICATIONS

Water
Sea water
Prefiltration for water treatment plants
Process water
Heat exchangers
Irrigation
Aquaculture
Protection of spray nozzles

Code	Description	Specs/ particular finishing	Connection In/Out	Connection drain	Flow rate from (l/h) ¹	Flow rate to (l/h) ¹	Quantity box	-
SPOPVC100MTWH	SPEEDBLUE SPO	White	1" BSP M	¾" BSP F	6000	12000	1	
SPOPVC112MTWH	SPEEDBLUE SPO	White	1" ½ BSP M	¾" BSP F	11000	25000	1	
SPOPVC200MTWH	SPEEDBLUE SPO	White	2" BSP M	¾" BSP F	18000	35000	1	

¹Max clean water flow rate in l/h at 20°C and differential pressure 0,5 bar.

Cyclon filters CYCLON PVC FILTERS SPEEDBLUE SP0

SELF CLEANING FILTERS CODE LIST

Model		Material		Connection IN/OUT		Finitura/specifica	
SP0		PVC	PVC	1" BSP M 1" 1/2 BSP M 2" BSP M	100MT 112MT 200MT	White	WH



Approximate picture. Connections and measures choice will lead to the assembly of a product which could differ from those shown in figure